



Professional power-feeding unit with variable speeds

# **VARIOSTEFF 3**

Safety device for a safe and effective workpiece feeding on different types of traditional wood-working machines



#### HIGH-QUALITY END PRODUCTS

3-wheel model : the ideal solution for the feeding of laths and medium or small-size workpieces. Thanks to the two infeed-wheels and the third outfeed one, the workpiece is constantly and evenly feeded althrough the working process, thus remarkably improving the quality of the end products.



### HIGHEST VERSATILITY

A wide range of variable speeds, that You can easily select by turning a knob. The ideal solution for those who often need to change the feeding rate. The speed selector on the motor unit allows a quick change of the feeding direction back and forth



### **PERFECT GRIP**

50-Shore wheels made of patented "Feeder Grip" rubber, providing the longest durability and the highest grip on the workingpiece

Improves the safety : the operator does not have to put his hands close to the tool Improves the finish quality, thanks to the constant and even feed-rate Feed-rate can be easily selected to meet every specific working need Easily adjustable to suit different sizes of work piece

## maggi-technology.com



# VARIOSTEFF 3

Worldwide after-sale service. Real-time, on-line remote assistance through a dedicated augmented reality APP. Spare-parts availability for up to 10 years, shipment within 24 hrs


# **DATA SHEET**

| Variable speeds                                       | from 3 to 18 mt/min (up to 33 mt/min optional) |
|---|--|
| N. of wheels  | 3  |
| Wheel diameter and thickness                          | 120 x 60 mm                                    |
| Motor   | 1 HP / 0,75 KW RPM 1400 /2800                  |
| Wheel suspention                                      | 20 mm  |
| Distance between wheels                               | <b>000</b> 182 mm - 133 m                      |
| Distance between first and last wheel                 | ○ ○ ○ 315 mm                                   |
| Overall dimensions and net weight of the feeding unit | 506 x 206 x 510 mm 31 Kg                       |
| Overall dimensions and net weight of the stand        | 540 x 910 mm 35 Kg                             |
| Package dimensions and gross weight (feeding unit)    | 670 x 570 x 330 mm 33 Kg                       |
| Package dimensions and gross weight ( stand)          | 800 x 330 x 330 mm 37 Kg                       |



### SAFETY AS A CORE VALUE

A power-feeder improves the safety as it feeds the workpiece close to the tool, while operator's hands are kept at a distance. Its effectiveness depends on specific design and manufacturing criteria. Maggi feeders are the only ones designed and manufactured in Italy and abiding by all EU safety norms.



# **UNIVERSAL STAND**

For easy positioning and adjusting of the feeding unit on the machine tool. It is easy to fix, stable and strong : foot, cross-shaped piece, pipe, joint and collar are made of cast-iron and the two columns are made of rectified steel of considerable thickness.

SERVICE +39 0571 635 433 service@maggi-technology.com

## SALES



MAGGI TECHNOLOGY Via delle Regioni, 299 50052 Certaldo (Firenze) Italia

+39 0571 635 474 sales@maggi-technology.com